BLITZ Tap Range Blitz Bath Taps Chrome



Specification				
Product Type:	Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Lever			
Connection Inlet:	3/4" BSP			
Connection Outlet:	Anti-splash			
Number of Tap Holes:	2			
Valve/Cartridge Type:	1/4 Turn 3/4" Ceramic Disc Valve			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.2 bar			
Maximum Dynamic Pressure (bar):	5 bar			
Maximum Hot Water Temperature °C:	65°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single			
Isolation Included:	No			

Features:

- Long life and easy to use 1/4 turn ceramic disc valves
- Metal back nuts for added durability
- 3/4" valve

Product Certifications:



WRAS Certificate No: 2006903 WRAS Expiry Date: 30/06/2025







For more products, visit our website: http://www.bristan.com



Dimensions (measurements in mm)





Flow Rates (I/min)								
System Pressure (bar)	0.2	0.5	1	2	3	5		
BTZ 3/4 C (mixed)	14.4	23.5	33.2	47	57.5	74.2		

TECHNICAL DATA SHEET



