FRM ES BAS C

FRAMMENTO Tap Range

Frammento Eco Start Basin Mixer with Clicker Waste Chrome



Specification				
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Flat Angled			
Connection Inlet:	1/2" BSP Flexible Tails			
Connection Outlet:	M24 Coin Slot 5lpm Aerator			
Number of Tap Holes:	1			
Valve/Cartridge Type:	28mm Cold Start Upper Seal Cartridge			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.5 bar			
Maximum Dynamic Pressure (bar):	5 bar			
Maximum Hot Water Temperature °C:	60°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single			
Isolation Included:	No			

Dimensions (measurements in mm)

Features:

- Eco Start technology saves energy by having cold water as the default central start position of the tap handle. Hot water is only activated when the tap lever is moved from the central position, so your boiler is not unnecessarily fired up.
- This tap has a flow regulator, which limits the flow of water to 5 litres per minute, reducing the amount of water you use.
- Long life ceramic cartridge for added durability and smooth control.
- Everything you need in the box including flexible tails and clicker waste so nothing to buy separately.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years.
 Salt spray tested to ensure added durability.
- 10-year parts and 1 year labour guarantee for peace of mind.
- Also available in black, brushed brass and gun metal.
- Co-ordinating Bathroom taps available.

Product Certifications:

Unified Water Label

♦4.7 l/min

	155	~ 1
	115	-
170		
		110
<u>, </u>	45	<u>V</u>

Flow Rates (I/min)							
System Pressure (bar)	0.5	1	2	3	5		
FRM ES BAS C (mixed)	2.6	3.7	4.6	4.7	5		

TECHNICAL DATA SHEET



BRISTAN