
## VT2 BSM C

# VANTAGE Tap Range Vantage 2 Bath Shower Mixer Chrome





			4
<b>-</b>	L		
-a		rac.	

- Long life and easy to use 1/4 turn ceramic disc valves
- Metal back nuts for added durability
- Includes 1.75m hose, rub-clean anti-limescale handset and wall bracket
- Minimum working pressure of 0.4

#### Specification **Product Type:** Bathroom Taps Main Construction Material: Brass **Deck Mounted** Mount Type: Handle Type: Lever Handles 3/4" BSP **Connection Inlet: Connection Outlet:** M28 Flow Straightener **Number of Tap Holes:** Valve/Cartridge Type: 3/4" Ceramic Disc Valve **Plumbing System Requirements:** Suitable for all plumbing systems Minimum Dynamic Pressure (bar): 0.4 bar Maximum Dynamic Pressure (bar): 5.0 bar 60°C Maximum Hot Water Temperature °C: Maximum Static Pressure (bar): 10 bar Flow Type: Single **Isolation Included:** No

Dimensions (measurements in mm)





#### **Product Certifications:**



WRAS Certificate No: 1912041 WRAS Expiry Date: 31/12/2024



**16.2 l/min** 

For more products, visit our website: http://www.bristan.com



Flow Rates (I/min)									
System Pressure (bar)	0.4	0.5	1	2	3	5			
Through Bath Filler (mixed)	22.6	25.3	35.8	50.6	62	80			
Through Handset (mixed)	5.9	6.6	9.4	13.2	16.2	20.9			

### TECHNICAL DATA SHEET



