
Product Data Sheet





White Wall Mounted WC Pan With Horizontal Outlet

Illustrated

E0005

S4270 Conceala 2 cistern 4.5 Litre single flush valve delay fill bottom supply and internal overflow, alternative height plastic flushbends E0021 White, plastic seat and cover S4512 Finger push button pneumatic, Stainless Steel for 31mm maximum thickness partition E0060

Support frame with bolts for wall hung WC pans

White wall mounted WC pan with horizontal outlet

Configuration options

S3624 Conceala 2 cistern 6/4 Litre dual flush valve top inlet and internal overflow, alternative height plastic flushbends S3625 Conceala 2 cistern 6/4 Litre dual flush valve bottom supply and internal overflow, alternative height plastic flushbends E0022 White, plastic seat only

S4399 Contemporary flush plate dual flush, unbranded for Conceala 2 cisterns

E4437 Contemporary flush plate dual flush, Ideal Standard logo for Conceala 2 cisterns

E4434 Flush plate dual flush for 820/880mm high In-wall system, Ideal Standard

E4433 Flush plate dual flush for 1100mm high In-wall system, Ideal Standard

In-wall system for WC, 880mm high for dual flush front E9292 operation, Ideal Standard

E9291 In-wall system for WC, 880mm high, dual flush, top operation, Ideal Standard

In-wall system for WC, 820mm high, dual flush, top E9293 operation, Ideal Standard

E9297 In-wall system for WC, 1100mm high, dual flush, front operation, Ideal Standard

Panekta outlet Connector, finned pattern to convert E3222 horizontal outlet WCs to P trap

E3221 Panekta outlet connector, finned pattern to convert horizontal outlet WCs to S or turned P trap

Material

Vitreous China

Weights

E0005 26.168KG S4270 2.66KG 3.14KG E0021 S4512 0.621KG E0060 4.2KG

Colours

White (01)

Standards

Vitreous china to BS 3402. WC pan to BS EN 997 & BS EN 33

Special Notes

E0060 support brackets screwed to floor within the duct, WC pan fixed to support brackets with bolts supplied and bolts screwed to back wall with brackets. Joint sealed with waterproof sealant (not supplied).

Designer

David Chipperfield



Tel: 0870 122 8822 Fax: 0870 122 8282 Email: info@idealspec.co.uk Web: www.idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Frequently used applications

Hotels Office

Public Building Pubs and Clubs

Residential Retail

Sports and Leisure
Accreditations WEPLS WTL
Powered by Ideal spec Date created:04/03/2013
Date Geateu.04/03/2013