## **TECHNICAL** DATA SHEET

### Hourglass Extension Tap Range 5 Hole Bath Shower Mixer Chrome

HOU 5HBSM C

10 bar static 0.4 – 5.0 bar

1/4 Turn 1/2" CD Valves

performance of mixer taps

1/2" BSP Inlet Connection


Nominally equal (balanced) inlet supply pressures are recommended for optimum

#### **Product** Specification

Product Code: Valve/Cartridge:

System:

Inlet type: Max Pressure: Operating Pressure Range:




0844 7016273

Delivery

#### Additional Information

• Chrome plated to BS EN 248:2002



Technical Advice:

For further information please call 0844 7016273 or email customercare@bristan.com

Guarantee:

WRAS:

5 years covering manufacturing faults.

#### Compliance / Approvals

Manufactured to comply with WRAS

#### **Flow** Rates (litres per minute)

Pressure	0.2	0.5	1.0	3.0	5.0
HOU 5HBSM C (Tap Outlet)	12.4	21.3	30.8	54.2	69.97
HOU 5HBSM C (Shower Outlet)	3.7	6.8	10.3	17	22.4

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG Telephone: 0844 701 6274 Facsimile: 0844 701 6275 Web Site: <u>www.bristan.com</u> Email: <u>enquire@bristan.com</u>

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.

# BRISTAN

