







Gas hob with front controls - for easy control of the 4 gas humers

- $\sqrt{}$ Powerful cooking at up to 3.3 kW.
- $\sqrt{}$ Continuous cast-iron pan supports for maximum stability and cooking convenience.
- $\sqrt{}$ The gas hob with a stainless-steel surface design.
- $\sqrt{\,}$ Design co-ordinated control dials easy to operate in an attractive design.

Features

Technical Data

Product name/family: gas hob w integrated controls

 $Construction\ type: Built-in$

Energy input : Gas

Total number of positions that can be used at the same time : 4 Required niche size for installation (HxWxD) : $45 \times 560-562 \times 10^{-2}$

480-492

Width of the product (mm): 582

Dimensions of the product (mm) : $45 \times 582 \times 520$

Dimensions of the packed product (HxWxD) (mm) : $141 \times 651 \times 578$

Net weight (kg): 10.094 Gross weight (kg): 11.0 Residual heat indicator: without Location of control panel: Hob front Basic surface material: Stainless steel Color of surface: Stainless steel Color of frame: Stainless steel Approval certificates: CE

Length of electrical supply cord (cm): 100

EAN code : 4242004236665 Electrical connection rating (W) : 1 Gas connection rating (W) : 7800

Current (A) : 3 Voltage (V) : 220-240 Frequency (Hz) : 50; 60



N 50, Gas hob, 60 cm, T26BB59N0

Feature:

Design

• Stainless steel

Special features

- Design co-ordinated control dials
- Ignition via control dials
- black cast iron pan supports with protective rubber feet

Power and size:

- 4 burner hob
- 3 burner + wok burner
- Left front: Standard burner 1.75 KW
- Left rear: Standard burner 1.75 KW
- Right rear: WOK burner 3.3 KW
- Right front: Economy burner 1 KW

Safety Features

- Flame failure safety device
- Factory set for connection to mains gas

Technical information

- \bullet Installation dimensions: (ID/W/D) 45 mm x 560 mm x 480 mm
- Appliance dimensions: (W/D) 582 mm x 520 mm
- Min. worktop thickness: 30 mm
- Power cord length 100 cm

Accessories

• LPG jets (28-30/37mbar) included

Dimensioned drawings

