QST BF C

QUEST Tap Range Quest Bath Filler Chrome



Specification					
Product Type:	Taps				
Main Construction Material:	Brass				
Mount Type:	Deck				
Handle Type:	Lever				
Connection Inlet:	3/4" BSP				
Connection Outlet:	M24 Flow Straightener				
Number of Tap Holes:	2				
Valve/Cartridge Type:	3/4" Ceramic Disc Valve - 1/4 turn				
Plumbing System Requirements:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.2 bar				
Maximum Dynamic Pressure (bar):	5.0 bar				
Maximum Hot Water Temperature °C:	65°C				
Maximum Static Pressure (bar):	10 bar				
Flow Type:	Single				
Isolation Included:	No				

Dimensions (measurements in mm)

Features:

- Long life and easy to use 1/4 turn ceramic disc valves
- Metal back nuts for added durability
- Easy to use metal handles
- Chrome plated to BS EN 248

Product Certifications:



WRAS Certificate No: 2106900 WRAS Expiry Date: 30/06/2026

For more products, visit our website: http://www.bristan.com



	 	217		143	
120					
		180	—	50	50

Flow Rates (I/min)										
System Pressure (bar)	0.2	0.5	1	2	3	5				
QST BF C (mixed)	20.5	32.5	45.9	64.9	79.5	102.6				

TECHNICAL DATA SHEET



