Product Data Sheet



415 -370 ---screw fixing centres --- 210---side inlet $\,\dashv$ 150 \vdash screw fixing centres lever hole option (RH or LH) + 170 ++35 (RH or LH) 275 230²⁸⁵ fixing front screws 85 ---bottom inlet option (RH or LH) -170

Conceala 2 Cistern Low Level 6 Litre Syphon Side Supply

.....

.....

Illustrated

S3617

Conceala 2 cistern 6 Litre single flush syphon side supply and internal overflow plastic flushbend, CP lever

Configuration options

Material

Standards

Plastic

Cistern to BS EN 14055

Weights

Colours

Special Notes

S3617 2.66KG

Lever supplied with cistern is suitable for 150mm max. wall thickness. Longer levers for thicker walls can be purchased.

Neutral / No Finish (67)

Frequently used applications

Education Factory

General Healthcare Hospitals (HTM64)

Hotels Office

Public Building Pubs and Clubs Residential Retail

Sports and Leisure

Armitage Shanks Tel: 0870 122 8822 Fax: 0870 122 8282 Email: info@idealspec.co.uk

Web: www.idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.



Date created:26/02/2013