Product Data Sheet



415 370 side screw fixing centres inlet → 150 ⊢ | -- 210 --option screw fixing centres 35-∔-275 285 fixing 195 front screws 85 bottom delayed fill inlet option bottom inlet option +170+170 + /35

Conceala 2 Cistern Universal Height 6 Litre Valve Side Supply

Illustrated

S3622 Conceala 2 cistern 6 Litre single flush valve side supply and internal overflow, alternative height plastic flushbends

S4512 Finger push button pneumatic, Stainless Steel for 31mm

maximum thickness partition

Configuration options

\$4513 Palm push button Pneumatic, Stainless Steel for 31mm

maximum thickness partition

S4464 Finger push button pneumatic, plastic for 31mm maximum

thickness partition

S4463 Palm push button Pneumatic, plastic for 31mm maximum

thickness partition

S4489 Finger push button pneumatic, Stainless Steel body for

400mm maximum wall thickness

SV316 3 metre tube

Material Standards

Plastic Cistern to BS EN 14055

Weights

S3622 2.66KG S4512 0.621KG

Colours

Neutral / No Finish (67)

Special Notes

Cistern is supplied with 800mm length of plastic air tube. An optional 3m length can be purchased where remote operation is required.

Capacity

6

.....

Frequently used applications

Education Factory

General Healthcare Hospitals (HTM64)

Hotels Office

Public Building Pubs and Clubs

Residential Retail

Sports and Leisure



Tel: 0870 122 8822 Fax: 0870 122 8282 Email: info@idealspec.co.uk Web: www.idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

ldeal spec

Date created:26/02/2013