### **Product Data Sheet**



#### top inlet 210 side option **−** 150 **⊢** screw fixing centres inlet option 35-20 275 285 fixing 195 front screws 85 +·170+ 35 access hole for bottom pneumatic tubing inlet option

# **Conceala 2 Cistern Universal** Height 6/4 Litre Valve, Top Inlet

### Illustrated

S3624 Conceala 2 cistern 6/4 Litre dual flush valve top inlet and internal overflow, alternative height plastic flushbends

S4397 Contemporary flush plate dual flush, Armitage Shanks

logo for Conceala 2 cisterns

### **Configuration options**

SV316 3 metre tube

E4437 Contemporary flush plate dual flush, Ideal Standard logo

.....

.....

for Conceala 2 cisterns

S4399 Contemporary flush plate dual flush, unbranded for

Conceala 2 cisterns

#### **Material Standards**

Plastic Cistern to BS EN 14055

#### Weights **Special Notes**

S3624 2.66KG S4397 1.005KG

**Colours** 

Neutral / No Finish (67)

Cistern is supplied with 2 x 800mm lengths of plastic air tubes. Optional 3m lengths can be

purchased where remote operation is required.

## Frequently used applications

Education Factory

General Healthcare Hospitals (HTM64)

Hotels Office

**Public Building** Pubs and Clubs

Residential Retail

Sports and Leisure

#### **Features Accreditations**

.....

**WEPLS** Water Saving

WTL



Tel: 0870 122 8822 Fax: 0870 122 8282 Email: info@idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Web: www.idealspec.co.uk

Idealspec

Date created:27/02/2013